

AC974 Series

Miniature Industrial Inherently Safe Accelerometer, Side Exit 2 Pin Mini-MIL Connector, 100 mV/g, ±10%



VIBRATION ANALYSIS HARDWARE



IECEx
IECEx SIR 15.0060X




Regulatory Information

Ex ia IIC T3/T4 Ga	Control Drawing INS10012
AEx ia IIC T3/T4 Ga	Ui = 28 Vdc li = 112 mA
CL I Groups A, B, C, D	Pi = 1W, Ci = 63.036nF, Li = 0µH
CL II Groups E, F, G; CL III	CSA 221421
CL I, Zone 0	Sira 15ATEX2152X
Operating Temperature Code: T4	Ex ia IIC T3 Ga
Ambient Temperature Range = -40 to 80°C	
Operating Temperature Code: T3	IECEx SIR 15.0060X
Ambient Temperature Range = -40 to 121°C	Ex ia IIC T3 Ga

AC974-1D

2 Pin Connector

Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common




Stock Product

AC974-2D

CB193 Integral Cable

Conductor	Polarity
White	(+) Signal/Power
Black	(-) Common




Built To Order

AC974-3D

CB296 Armored Integral Cable


Conductor	Polarity
White	(+) Signal/Power
Black	(-) Common



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC974	M/AC974	Environmental		
Sensitivity (±10%)		100 mV/g	Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±3dB)	36-600,000 CPM	0.6-10000 Hz	Maximum Shock Protection		5,000 g, peak
Dynamic Range		± 50 g, peak	Electromagnetic Sensitivity		CE
Electrical			Sealing		Welded, Hermetic
Settling Time		<2.5 Seconds	Physical		
Voltage Source (IEPE)		18-28 VDC	Sensing Element		PZT Ceramic
Constant Current Excitation		2-10 mA	Sensing Structure		Shear Mode
Spectral Noise @ 10 Hz		30 µg/√Hz	Weight	2.1 oz	60 grams
Spectral Noise @ 100 Hz		4 µg/√Hz	Case Material		316L Stainless Steel
Spectral Noise @ 1000 Hz		2 µg/√Hz	Mounting		1/4-28
Output Impedance		< 100 ohm	Connector (Non-Integral)		2 Pin mini-MIL
Case Isolation		>10 ⁸ ohm	Resonant Frequency	1,920,000 CPM	32000 Hz
			Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
			Mounting Hardware	1/4-28 Captive Bolt	M6x1 Captive Bolt
			Calibration Certificate		CA10

Typical Frequency Response



Backed by our Unconditional Lifetime Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900